## Replacing the Battery Pack Inside the Body

• Unscrew the body and then slide out the old battery pack.



#### Choosing between 4-Levels, Red and SOS of output

- Press the push button every time to choose the desired output level: I- output at 10%, II-output at 25%, III-output at 50%, IV-output at 100%.
- For 4-Levels setting, press the push button each time to change the level of output accordingly.
- For Red LED setting, press the push button continuously two times to get red effect and back to normal when you press the push button once again.
- For SOS setting, press the push button for 2 sec to get SOS effect and back to normal when you press the push button once again.
- For OFF setting, press the push button one time after 1 sec of level selection or press the push button five times after 4-Levels setting.

# Battery level indicator built-in

 Color of LEDs change from the time being. It will change from blue to green and green to red. When the red led flashes, it reminds people to charge up the battery.



## **Charging the Battery**

- Place the Li ion battery inside the Smart Quick Charger. There is no need to discharge after use.
- Charge time will depend on the remaining capacity in the battery and the surrounding temperature.



# Maintenance and Transportation

- After each dive, always rinse with fresh water. If the diving light will not be used for a prolonged period of time (more than a month), take out the LED light module.
- In rare cases of flooding, discontinue use. Turn the light off immediately and rinse with fresh water. Let the components dry completely, and return it to Bigblue for service.
- Flooding damage cannot be repaired on site.

#### Clean the light and Lubricate the O-Ring

- For good practice, put the light into fresh water for few hours after every dive.
- Dry it out and put the silicone crease on the O-Ring. Ready for other dive.

## Mounting the Goodman Glove



Adapter plate



Fix the plate with the supplied screw



Goodman Glov



Put the Velcro through the slot of the plate and through the loop



Tighten by pulling the Velcro

# Setup Using Photographic Arms and Clips\*

- Twist the knobs on the clips anticlockwise until loosened.
- Insert the ball joint of the Video Light in between the gaps of the clips.
- Once the ball joint is inserted into the clips, secure its position by twisting the knobs on the clips clockwise.



\*Photographic Arms and Clips are sold separately

#### **Technical Specifications**

Light Source Light Output

Light output (Red color mode) Casing Material Power Source Angle of Light Beam Color Temperature Burn Time

Maximum Depth
Size:
Weight in Air
Buoyancy in Sea water
Switching System
Front Glass
Lanyard

6 x XML LED + 4 x XPE Red LED 280 Lm ( level I), 700 Lm ( level II) 1400 Lm ( level III) , 2800 Lm ( level IV) 200 Lm

Aluminum alloy. Anti-corrosive anodized Li ion Rechargeable battery pack 32650 120° wide beam 6500K

1.5hrs ( level IV), 3 hrs( level III) 6 hrs(level II) and 15hrs ( level I)

100m tested
Dia. 52.5 x L. 118.1mm
343g (including battery)

-169g (including battery)
Push button with battery indicator

Tempered optical glass Included

Specifications subject to change without prior notice



electrical and electronic products. household waste. Check with your local collection system for

- Do not dispose of your rechargeable battery with general disassemble or modify.
  - Do not dispose of in fire, Do not neat, deform, solder, damaged or subjected to shock.
  - Do not operate the battery or the charger if it has been use for an extended period of time.
- $\bullet$  Remove the battery from the light if it is not going to be in strong mechanical shock.
- The Li ion battery should not be dropped or be subjected to metal objects to avoid short circuit.
- · When storing or carrying the battery, avoid direct contact with battery to leak or rupture. pressure. If the temperature is too high, it may cause the
  - cover the charger with a blanket, or place under heavy • Do not charge near hot temperature, under direct sunlight,
  - battery and the surrounding temperature. • Charge time will depend on the remaining charge in the
  - result in fire or electric shock. Using incompatible adapters may damage the charger or
  - Use only the power adapters supplied with the charger.
  - Fully charge the batteries before using for the first time. connection can damage the unit.
  - Connect with the correct polarity (+ and -) only, incorrect rechargeable battery only.
  - Intended to be used with the custom-made 32650 Li ion

Using the rechargeable Li ion battery

hands-free operation Goodman glove for





cools on, power comes back on. above 70°C. As soon as the light on land, or exposure to temperatures power in case of prolonged use by automatically cutting off its prevents the light from overheating • The thermal protection system

> oberation underwater. · Sturdy glove for hands-free

bunoous a warmer color tone for video · Kemovable yellow filter to achieve

tocusing performance, little creatures and enhancing • Built in red LED for viewing shy

enabling you to charge in a few comes with a smart charger, • Li ion rechargeable battery design

Features

insulated from all internal parts, eliminating the risk of the power output levels, but it is also designed to be

- The putton not only makes it easy to change between
  - 100%, 50%, 25% and 10% of total brightness. I pe tour levels power output lets you choose between

underwater surrounding while diving.

- The 6500K white light reflects the true vibrant colors of the
- of 50,000 hours, reducing the need for frequent bulb

• The LEDs are maintenance-free, they guarantee a burn time

video shoot results,

120° perfectly even light spot, making it a must for the best • 6 x ultra high intensity LED delivers 2800 lumens, and an

Congratulations on your purchase of our Bigblue product. The Bigblue Diving Light uses carefully selected materials that have met rigorous industry standards. With innovative manufacturing processes, and strict quality controls, we guarantee the reliability of all Bigblue diving products.

#### Introduction

The VL 2800P delivers a stunning 2800 lumens light output 6 x ultra high intensity LED and 200 lumens red light output 4 x high intensity red LED. It is a compact and versatile diving light with wide and even light beam, best suitable for video shooting. Combined with the self-contained 32650 Li ion rechargeable battery design, it actualizes the super convenience and performance which can meet the needs of discerning video professionals.



## **Limited Warranty**

- 1. Bigblue guarantees the proper operation of this product by the original retail purchaser under normal and intended use.
- 2. This warranty applies only to the original retail purchaser, which does not apply to commercial or rental use, nor is it transferable
- 3. If the original retail purchaser detects defect in the materials or workmanship, return the product together with proof of purchase indicating the date of purchase to an authorized Bigblue dealer
- 4. The warranty covers a period of up to one (1) year from the date of purchase. Warranty for rechargeable battery pack is valid for six (6) months only.
- 5. This limited warranty is in lieu of all other warranties. No other person or party is authorized to assume for Bigblue any other liability in connection with the sales of this product.
- 6. This warranty will be voided if the product or any of its parts have been tempered with, repaired, modified, transformed, adapted or damaged without authorization by Bigblue.
- 7. This warranty does not cover parts subjected to normal wear and tear, including and is not limited to the following: O-rings, battery pack, front glass (surface scratch or damage on impact).
- 8. This warranty does not cover damages due to impact, use in chlorinated or polluted waters, and extended exposure to heat

#### **Bossk International Company Limited**

Tel: (852) 3568 0773

Email: customerservice@bigblue.com.hk

Web: www.bigblue.com.hk MADE IN CHINA Patent Pending





INSTRUCTION MANUAL

