



Taking Innovation to New Depths

2019



# C O N T E N T

AL250 ..... P.35	Batteries ..... P.64	TL2600P ..... P.26
AL450WM Tail ..... P.36	Camera Arms ..... P.70	TL3500P ..... P.27
AL450NM Tail ..... P.37	Camera Clips & Accessories ..... P.70	TL3500P Supreme ..... P.34
ALI100RAFO II ..... P.40	Camera Trays ..... P.62	TL4800P ..... P.28
ALI200NP II ..... P.42	Camera Filters ..... P.60	TL4800PC Slim ..... P.30
ALI200WVP II ..... P.43	CB6500P ..... P.20	TL8000P ..... P.32
ALI200XWP II ..... P.44	CB9000P ..... P.22	VL4200P ..... P.2
ALI200NP Tail II ..... P.38	CB15000P ..... P.24	VL8000P Tri Color ..... P.4
ALI200WVP Tail II ..... P.39	CF450 II ..... P.46	VLI0000P ..... P.6
ALI800P Tri Color II ..... P.46	CF1200P II ..... P.49	VLI5000P Pro Mini ..... P.8
AL2600XWP II ..... P.47	Chargers ..... P.64	VLI5000P Pro Mini Tri Color ..... P.10
	Combo Packs ..... P.56	VL33000P II ..... P.12
	Easy Clip Lights ..... P.54	VTL2600P ..... P.14
	Easy Release Mount Series ..... P.68	VTL3800P ..... P.15
	Float Arms, Flexi Arms ..... P.69	VTL8000P ..... P.16
	Fluorodive Kits ..... P.60	VTL8000PC Slim ..... P.18
	Gloves, Hoods & Handles ..... P.65	
	HL450N ..... P.50	
	HL450XW ..... P.51	
	HL1000N ..... P.52	
	HL1000XW ..... P.53	
	Light Filters ..... P.66	
	Light Head ..... P.45	
	Outdoor Dry Bags ..... P.68	
	Protective Case Series ..... P.59	
	RGB White II ..... P.41	
	Red Spot Light & Green Spot Light ..... P.58	
	Snoots ..... P.66	
	Spring Cord ..... P.67	



# VL4200P

Li ion Rechargeable Battery LED Video Light



Available in 3 colors

## SPECIFICATIONS

Light source	6 x XML LED + 4 x XPE Red LED
Light output (Flood beam mode)	420 Lm (level I), 1050 Lm (level II) 2100 Lm (level III), 4200 Lm (level IV)
Light output (Red color mode)	200 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 32650
Angle of light beam	120° wide beam
Color temperature	6500K
Burn time	1.5 hrs (level IV), 3 hrs (level III) 6 hrs (level II) and 15 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 44 x L 121.1 mm
Weight in air	318 g (including battery)
Buoyancy in seawater	-167 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



Sturdy glove for hands-free operation underwater



4 levels of brightness for Flood beam mode, 1 level of brightness of Red color mode and SOS controlled by a reliable push button design



BATCELL 32650 Li ion Rechargeable Battery




Built-in red color led enhances focusing performance



Comes with ball joint for easy system setup



Removable yellow filter enhances warmer color tone



Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color



Come with random color outdoor dry bag

# VL8000P TRI COLOR

Li ion Rechargeable Battery High Power LED  
Video Light with Three Color Output




## SPECIFICATIONS

Light source	15 x XML LED + 6 x XPE Red LED
Light output (Cool white mode)	2000 Lm (level I), 4000 Lm (level II) 8000 Lm (level III)
Light output (Warm white mode)	1000 Lm (level I), 2000 Lm (level II) 4000 Lm (level III)
Light output (Red white mode)	500 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL18650x4
Angle of light beam	120° wide beam
Color temperature	6500K cool white and 5500K warm white
Burn time	3 hrs (level III), 6 hrs (level II) and 12 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 55.4 x L. 130.6mm
Weight in air	457 g (including battery)
Buoyancy in seawater	-173 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



3 Levels of brightness  
for cool white mode,  
3 Levels of brightness  
for warm white mode  
1 level of brightness of  
Red color mode and SOS  
controlled by a reliable  
push button design




Battery level indicator  
built-in: Blue color /  
Green color / Red  
color / Flash Red color



BATCELL18650x4  
Li ion Rechargeable  
Battery



Built-in red color led  
enhances focusing  
performance



Built-in yellow color led  
enhances warmer color  
tone



Sturdy glove for  
hands-free operation  
underwater



Comes with ball joint  
for easy system setup



Come with  
random color  
outdoor dry bag



# VL10000P

Li ion Rechargeable Battery High Power  
LED Video Light




## SPECIFICATIONS

Light source	15 x XML LED + 6 x XPE Red LED
Light output	1000 Lm (level I), 2500 Lm (level II) 5000 Lm (level III), 10000 Lm (level IV)
Light output ( Red color mode)	500 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL18650x4
Angle of light beam	120° wide beam
Color temperature	6500K
Burn time	2.5 hrs (level IV), 5 hrs (level III) 10 hrs (level II) and 25 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 55.4 x L. 130.6mm
Weight in air	457g (including battery)
Buoyancy in seawater	-173g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included




4 Levels of brightness,  
1 level of brightness of  
Red color mode and  
SOS controlled by a  
reliable push button  
design



Battery level indicator  
built-in: Blue color /  
Green color / Red  
color / Flash Red color



BATCELL18650x4  
Li ion Rechargeable  
Battery



Built-in red color led  
enhances focusing  
performance



Removable yellow  
filter enhances  
warmer color tone



Sturdy glove for  
hands-free operation  
underwater



Comes with ball joint  
for easy system setup



Come with  
random color  
outdoor dry bag

# VL15000P PRO MINI

Li ion Rechargeable Battery Super  
Power LED Video Light



15000  
lumens



**15000  
LUMENS**  
Angle of light beam  
**160° wide beam**

## SPECIFICATIONS

Light source	24 x XML LED + 8 x XPE Red LED
Light output	1500 Lm (level I), 3750 Lm (level II) 7500 Lm (level III), 15000 Lm (level IV)
Light output (Red color mode)	1000 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL18650x7
Angle of light beam	160° wide beam
Color temperature	6500K
Burn time	2 hrs (level IV), 4 hrs (level III) 8hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 70 x L. 131 mm
Weight in air	754 g (including battery)
Buoyancy in seawater	-295 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass



4 levels of brightness  
1 level of brightness of  
Red color mode and  
SOS controlled by a  
reliable push button  
design



Battery level indicator  
built-in: Blue color /  
Green color / Red  
color / Flash Red color



BATCELL18650x7  
Li ion Rechargeable  
Battery



Built-in red color led  
enhances focusing  
performance



24pcs XML LED  
to provide  
15000 lumens



Comes with  
ball joint for  
easy system  
setup



Ergonomic  
aluminum handle  
comes in a  
package



Come with  
protective case  
for VL 15000P  
Pro Mini.



FILFLUORO15000  
Fluorodive filter for  
VL 15000P Pro Mini.  
Sold separately.



# VL15000P PRO MINI TRI COLOR

Li ion Rechargeable Battery Super Power LED  
Video Light with Three Color Output



**15000  
LUMENS**  
Angle of light beam  
**160° wide beam**

## SPECIFICATIONS

Light source	32 x XML LED + 8 x XPE Red LED
Light output (Cool white mode)	3750 Lm (level I), 7500 Lm (level II) 15000 Lm (level III)
Light output (Warm white mode)	1500 Lm (level I), 3000 Lm (level II) 6000 Lm (level III)
Light output (Red color mode)	1000 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL18650x7
Angle of light beam	160° wide beam
Color temperature	6500K cool white and 5500K warm white
Burn time	2 hrs (level III), 4 hrs (level II) and 8 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 70 x L. 131 mm
Weight in air	769 g (including battery)
Buoyancy in seawater	-310 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass



Battery level indicator built-in:  
Blue color / Green color / Red color /  
Flash Red color



BATCELL18650x7  
Li ion Rechargeable  
Battery



Built-in red color  
led enhances  
focusing  
performance



Built-in  
yellow color  
led enhances  
warmer  
color tone



Come with  
protective case  
for VL 15000P  
Pro Mini Tri Color.



Ergonomic  
aluminum  
handle comes  
in a package



FILFLUORO15000  
Fluoride filter for  
VL 15000P Pro Mini  
Tri Color.  
Sold separately.



Comes with  
ball joint for  
easy system  
setup



3 Levels of brightness for  
cool white mode, 3 Levels  
of brightness for warm  
white mode, 1 level of  
brightness of Red color  
mode, and SOS controlled  
by a reliable push button  
design

# VL33000P II

Li ion Rechargeable Battery  
Ultra Power LED Video Light



## SPECIFICATIONS

Light source	45 x XML LED + 10 x XPE Red LED
Light output	3300 Lm (level I), 8250 Lm (level II) 16500 Lm (level III), 33000 Lm (level IV)
Light output (Red color mode)	1200 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL 21700x8
Angle of light beam	160° wide beam
Color temperature	6500K
Burn time	1.5 hrs (level IV), 3 hrs (level III) 6 hrs (level II) and 15 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 85 x L 144.6mm
Weight in air	1391g (including battery)
Buoyancy in seawater	-597g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass

The Most  
Brightness  
**33000  
LUMENS**  
Angle of light beam  
**160°**



4 levels of brightness,  
1 level of brightness of  
Red color mode and  
SOS controlled by a  
reliable push button  
design



Battery level indicator  
built-in: Blue color /  
Green color / Red  
color / Flash Red color



Easy to charge up the  
battery pack  
BATCELL 21700x8



Built-in red color led  
enhances focusing  
performance



45pcs XML LED to  
provide 33000 lumens



Comes with ball joint  
for easy system setup



Ergonomic aluminum  
handle comes in a  
package



Come with  
protective case  
for VL 33000P II.



# VTL2600P

Li ion Rechargeable Battery LED Video / Tech Light



Available in 2 colors

**100°**  
Wide Beam  
**10°**  
Narrow Beam



4 levels of brightness for Flood beam mode, 1 level of brightness for Spot beam mode and 1 level of brightness for Red color mode controlled by a reliable push button design

## SPECIFICATIONS

Light source	7 x LED + 2 x XPE Red LED
Light output (Flood beam mode)	260 Lm (level I), 650 Lm (level II) 1300 Lm (level III), 2600 Lm (level IV)
Light output (Spot beam mode)	1000 Lm
Light output (Red color mode)	100 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 32650
Angle of light beam	100° wide beam and 10° narrow beam
Color temperature	6500K
Burn time	1.5 hrs (level IV), 3 hrs (level III) 6 hrs (level II) and 15 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 44 x L. 128.7 mm
Weight in air	339 g (including battery)
Buoyancy in seawater	-177 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



Sturdy glove for hands-free operation underwater



Removable yellow filter enhances warmer color tone



Built-in red color led enhances focusing performance



Angle of light beam



Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color



Comes with ball joint for easy system setup



BATCELL 32650 Li ion Rechargeable Battery



Come with random color outdoor dry bag

# VTL3800P

Li ion Rechargeable Battery LED Video / Tech Light



**120°**  
Wide beam  
**10°**  
Narrow beam



4 levels of brightness for Flood beam mode, 1 level of brightness for Spot beam mode and 1 level of brightness for Red color mode controlled by a reliable push button design

## SPECIFICATIONS

Light source	7 x XML LED + 2 x XPE Red LED
Light output (Flood beam mode)	380 Lm (level I), 950 Lm (level II) 1900 Lm (level III), 3800 Lm (level IV)
Light output (Spot beam mode)	1200 Lm
Light output (Red color mode)	100 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 32650
Angle of light beam	120° wide beam and 10° narrow beam
Color temperature	6500K
Burn time	1.5 hrs (level IV), 3 hrs (level III) 6 hrs (level II) and 15 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 55.5 x L. 140.6 mm
Weight in air	432 g (including battery)
Buoyancy in seawater	-205 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



Sturdy glove for hands-free operation underwater



Removable yellow filter enhances warmer color tone



Built-in red color led enhances focusing performance



Angle of light beam



Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color



Comes with ball joint for easy system setup



BATCELL 32650 Li ion Rechargeable Battery



Come with random color outdoor dry bag



# VTL8000P

Li ion Rechargeable Battery High Power LED Video / Tech Light

**120°**  
Wide beam  
**10°**  
Narrow beam



## SPECIFICATIONS


Light source	11 x XML LED + 6 x XPE Red LED
Light output ( Flood beam mode )	800 Lm (level I), 2000 Lm (level II) 4000 Lm (level III), 8000 Lm (level IV)
Light output ( Spot beam mode)	1200 Lm
Light output ( Red color mode)	500 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL18650x4
Angle of light beam	120° wide beam and 10° narrow beam
Color temperature	6500K
Burn time	3 hrs (level IV), 6 hrs (level III) 12 hrs (level II) and 30 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 63x L. 150.3mm
Weight in air	548g (including battery)
Buoyancy in seawater	-203g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color



Angle of light beam



Built-in red color led enhances focusing performance



4 Levels of brightness for Flood beam mode, 1 level of brightness for Spot beam mode and 1 level of brightness for Red color mode controlled by a reliable push button design



Removable yellow filter enhances warmer color tone



Sturdy glove for hands-free operation underwater



Comes with ball joint for easy system setup



BATCELL18650x4 Li ion Rechargeable Battery



Come with random color outdoor dry bag



# VTL8000PC SLIM

Li ion Rechargeable Battery  
High Power LED Video/Tech Light  
with Battery Canister



## SPECIFICATIONS


Light source	11 x XML LED + 6 x XPE Red LED
Light output ( Flood beam mode )	800 Lm (level I), 2000 Lm (level II) 4000 Lm (level III), 8000 Lm (level IV)
Light output ( Spot beam mode )	1200 Lm
Light output ( Red color mode )	500 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL 18650x8
Angle of light beam	120° wide beam and 10° narrow beam
Color temperature	6500K
Burn time	6 hrs (level IV), 12 hrs (level III) 24 hrs (level II) and 60 hrs (level I)
Maximum depth	100 m tested
Size (Light head)	Dia. 63x L. 106.5mm
Size (Canister)	Dia. 55 x L. 181.5mm
Weight in air (Light head)	317g
Weight in air (Canister)	713g
Buoyancy in seawater (Light head)	-101g
Buoyancy in seawater (Canister)	-267g
Switching system	Push button with battery indicator
Front glass	Tempered optical glass



Comes with  
ball joint for  
easy system  
setup



BATCELL  
18650x8  
Li ion  
Rechargeable  
Battery



Battery level  
indicator built-in:  
Blue color /  
Green color /  
Red color /  
Flash Red color



Built-in red  
color led  
enhances  
focusing  
performance



Slim fit  
Goodman  
handle with  
connector.  
Comes in  
a package



Removable  
yellow  
filter  
enhances  
warmer  
color tone



Easy to  
charge up  
the canister



Angle of  
light beam



VTL8000PCLH  
light head and  
Canister for  
VTL8000PC  
Slim can buy  
seperately.



90 degree  
sidemount  
connector  
cable.  
Sold seperately.



Come with  
protective case  
for VTL 8000  
PC Slim



4 Levels of brightness for  
Flood beam mode, 1 level  
of brightness for Spot  
beam mode and 1 level  
of brightness for Red  
color mode controlled  
by a reliable push  
button design

# CB6500P

Li ion Rechargeable Battery High Power  
LED Video Light with High Color Rendering Index




## SPECIFICATIONS

Light source	COB LED + 6 x XPE Red LED
Light output	650 Lm (level I), 1625 Lm (level II) 3250 Lm (level III), 6500 Lm (level IV)
Light output (Red color mode)	500 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL 21700x4
Angle of light beam	120° wide beam
Color temperature	5000K
Color Rendering Index	Ra 85
Burn time	2 hrs (level IV), 4 hrs (level III) 8 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 63 x L. 134.6mm
Weight in air	653g (including battery)
Buoyancy in seawater	-272g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



4 Levels of brightness,  
1 level of brightness of  
Red color mode and  
SOS controlled by a  
reliable push button  
design




Battery level indicator  
built-in: Blue color /  
Green color / Red color  
/ Flash Red color



BATCELL 21700x4  
Li ion Rechargeable  
Battery



Snoot 63  
Snoot connector for  
CB6500P.  
Sold separately.



Built-in red color led  
enhances focusing  
performance



Sturdy glove for  
hands-free operation  
underwater



Comes with ball joint  
for easy system setup



Come with  
random color  
outdoor dry bag



# CB9000P

Li ion Rechargeable Battery High Power  
LED Video Light with High Color  
Rendering Index



## SPECIFICATIONS

Light source	COB LED + 6 x XPE Red LED
Light output	900 Lm (level I), 2250 Lm (level II) 4500 Lm (level III), 9000 Lm (level IV)
Light output (Red color mode)	500 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL 21700x4
Angle of light beam	120° wide beam
Color temperature	5000K
Color Rendering Index	Ra 85
Burn time	1.5 hrs (level IV), 3 hrs (level III) 6 hrs (level II) and 15 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 63 x L 134.6mm
Weight in air	654g (including battery)
Buoyancy in seawater	-273g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



4 Levels of brightness,  
1 level of brightness of  
Red color mode and  
SOS controlled by a  
reliable push button  
design



Battery level indicator  
built-in: Blue color /  
Green color / Red color  
/ Flash Red color



BATCELL 21700x4  
Li ion Rechargeable  
Battery



Snoot 63  
Snoot connector for  
CB 9000P.  
Sold separately.



Built-in red color led  
enhances focusing  
performance



Sturdy glove for  
hands-free operation  
underwater



Comes with ball joint  
for easy system setup



Come with  
random color  
outdoor dry bag

# CB15000P

Li ion Rechargeable Battery Super Power  
LED Video Light with High Color  
Rendering Index



**15000  
LUMENS**  
Angle of light beam  
**160°** wide beam

## SPECIFICATIONS

Light source	COB LED + 8 x XPE Red LED
Light output	1500 Lm (level I), 3750 Lm (level II) 7500 Lm (level III), 15000 Lm (level IV)
Light output ( Red color mode)	1000 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL18650x7
Angle of light beam	160° wide beam
Color temperature	5000K
Color Rendering Index	Ra 85
Burn time	1.5 hrs (level IV), 3 hrs (level III) 6 hrs (level II) and 15 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 70 x L. 131mm
Weight in air	773g (including battery)
Buoyancy in seawater	-314g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass



4 levels of brightness  
1 level of brightness of  
Red color mode and  
SOS controlled by a  
reliable push button  
design



Battery level indicator  
built-in: Blue color /  
Green color / Red  
color / Flash Red color



BATCELL18650x7  
Li ion Rechargeable  
Battery



Built-in red color led  
enhances focusing  
performance



COB LED  
to provide  
15000 lumens



Comes with  
ball joint for  
easy system  
setup



Ergonomic  
aluminum handle  
comes in a  
package



Come with  
protective case  
for CB15000P .



FILFLUORO15000  
Fluorodrive filter for  
CB15000P.  
Sold separately.




# TL2600P

Li ion Rechargeable Battery  
LED Tech Light



Available in 2 colors



Battery level indicator  
built-in: Blue color /  
Green color / Red color  
/ Flash Red color

## SPECIFICATIONS

Light source	3 x LED
Light output	260 Lm (level I), 650 Lm (level II) 1300 Lm (level III), 2600 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 32650
Angle of light beam	10° narrow beam
Color temperature	6500K
Burn time	1.5 hrs (level IV), 3 hrs (level III) 6 hrs (level II) and 15 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 50x L. 130 mm
Weight in air	359 g (including battery)
Buoyancy in seawater	-188 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



4 Levels of brightness  
and SOS controlled by  
a reliable push button  
design



Ergonomic aluminum  
handle comes in a  
package



BATCELL 32650 Li ion  
Rechargeable Battery



Goodman handle  
with connector or  
Slim fit Goodman handle  
with connector. Sold  
separately.




Sturdy Goodman Glove  
for handy Tech-diver  
operation



Come with  
random color  
outdoor dry bag

# TL3500P

Li ion Rechargeable Battery  
LED Tech Light



Battery level indicator  
built-in: Blue color /  
Green color / Red color  
/ Flash Red color

## SPECIFICATIONS

Light source	3 x XML LED
Light output	350 Lm (level I), 875 Lm (level II) 1750 Lm (level III), 3500 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 32650
Angle of light beam	10° narrow beam
Color temperature	6500K
Burn time	1.5 hrs (level IV), 3 hrs (level III) 6 hrs (level II) and 15 hrs (level I)
Maximum depth	150 m tested
Size	Dia. 63x L. 135.6 mm
Weight in air	447 g (including battery)
Buoyancy in seawater	-217 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



4 Levels of brightness  
and SOS controlled by  
a reliable push button  
design



Ergonomic aluminum  
handle comes in a  
package



BATCELL 32650 Li ion  
Rechargeable Battery



Goodman handle  
with connector or  
Slim fit Goodman handle  
with connector. Sold  
separately.



Sturdy Goodman Glove  
for handy Tech-diver  
operation



Come with  
random color  
outdoor dry bag

# TL4800P

Li ion Rechargeable Battery High Power  
LED Tech Light



## SPECIFICATIONS

Light source	4 x XML LED
Light output	480 Lm (level I), 1200 Lm (level II) 2400 Lm (level III), 4800 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL18650x4
Angle of light beam	10° narrow beam
Color temperature	6500K
Burn time	2 hrs (level IV), 4 hrs (level III) 8 hrs (level II) and 20 hrs (level I)
Maximum depth	150 m tested
Size	Dia. 72 x L. 150.3mm
Weight in air	596 g (including battery)
Buoyancy in seawater	-222 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



4 Levels of  
brightness and  
SOS controlled  
by a reliable push  
button design




BATCELL18650x4  
Li ion Rechargeable  
Battery



Sturdy Goodman  
Glove for handy  
Tech-dive operation



Ergonomic aluminum  
handle comes in a  
package



Battery level  
indicator built-in:  
Blue color /  
Green color / Red  
color / Flash Red  
color



Goodman handle with  
connector or  
Slim fit Goodman  
handle with connector.  
Sold separately.



Come with  
random color  
outdoor dry bag



# TL4800PC SLIM

Li ion Rechargeable Battery  
High Power LED Tech Light with  
Battery Canister



**4800**  
lumens



## SPECIFICATIONS

Light source	4 x XML LED
Light output	480 Lm (level I), 1200 Lm (level II) 2400 Lm (level III), 4800 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL18650x8
Angle of light beam	10° narrow beam
Color temperature	6500K
Burn time	7 hrs (level IV), 14 hrs (level III) 28 hrs (level II) and 70 hrs (level I)
Maximum depth	100 m tested
Size (Light head)	Dia. 72 x L 88.3mm
Size (Canister)	Dia. 55 x L 181.5mm
Weight in air (Light head)	380g
Weight in air (Canister)	713g
Buoyancy in seawater (Light head)	-134g
Buoyancy in seawater (Canister)	-267g
Switching system	Push button with battery indicator
Front glass	Tempered optical glass



4 Levels of brightness  
and SOS controlled by  
a reliable push button  
design



Battery level indicator  
built-in: Blue color /  
Green color / Red  
color / Flash Red color



BATCELL18650x8  
Li ion Rechargeable  
Battery



Ergonomic  
aluminum handle  
comes in a  
package



Slim fit Goodman  
handle with con-  
nector. Comes in  
a package



Easy to charge  
up the canister



90 degree  
sidemount  
connector cable.  
Sold seperately.



TL4800PCLH light  
head and Canister  
for TL4800PC Slim  
can buy seperately.



Come with  
protective case  
for TL 4800  
PC Slim

# TL8000P

Li ion Rechargeable Battery Super  
Power LED Tech Light



8000  
lumens



## SPECIFICATIONS

Light source	8 x LED
Light output	800 Lm (level I), 2000 Lm (level II) 4000 Lm (level III), 8000 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL I8650x7
Angle of light beam	10° narrow beam
Color temperature	6500K
Burn time	2 hrs (level IV), 4 hrs (level III) 8 hrs (level II) and 20 hrs (level I)
Maximum depth	150 m tested
Size	Dia. 72 x L 138.8 mm
Weight in air	784 g (including battery)
Buoyancy in seawater	-290 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass



4 levels of brightness  
and SOS controlled by  
a reliable push button  
design



Battery level indicator  
built-in: Blue color /  
Green color / Red  
color / Flash Red color



BATCELL I8650x7  
Li ion Rechargeable  
Battery



Ergonomic aluminum  
handle comes in a  
package



Slim fit Goodman  
handle with connector.  
Comes in a  
package



Come with  
random color  
outdoor dry bag



# TL3500P SUPREME

Li ion Rechargeable Battery  
LED Tech Light

ERM  
EASY RELEASE  
MOUNT

3500  
lumens



Battery level indicator  
built-in: Blue color /  
Green color /  
Red color /  
Flash Red color

## SPECIFICATIONS

Light source	3 x XML LED
Light output	350 Lm (level I), 875 Lm (level II) 1750 Lm (level III), 3500 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL I8650x4 SUPREME
Angle of light beam	10° narrow beam
Color temperature	6500K
Burn time	3 hrs (level IV), 6 hrs (level III) 12 hrs (level II) and 30 hrs (level I)
Maximum depth	150 m tested
Size	Dia. 63x L. 119 mm
Weight in air	517 g (including battery)
Buoyancy in seawater	-221 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



4 Levels of brightness  
and SOS controlled by  
a reliable push button  
design



Ergonomic aluminum  
handle comes in a  
package



BATCELL I8650x4 SUPREME  
Li ion Rechargeable  
Battery



Goodman handle  
with connector or  
Slim fit Goodman  
handle with connector.  
Sold separately.



Sturdy Goodman Glove  
for handy Tech-dive  
operation



Come with  
random color  
outdoor dry bag

# AL250

Multi-Function Aluminum LED Light

250  
lumens



## SPECIFICATIONS

Light source	1 x XPG LED
Light output	250 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	2xAA alkaline or Ni-MH batteries
Angle of light beam	8° narrow beam
Color temperature	6500K
Burn time	Up to 2 hrs
Maximum depth	100 m tested
Size	Dia. 28x L. 147.8 mm
Weight in air	135 g (including battery)
Buoyancy in seawater	-85 g (including battery)
Front glass	Tempered optical glass
Lanyard	Included



Light is suitable for multi-function



Operate with 2xAA  
batteries



Our light can fit in  
glove or pouch. Sold  
separately.



Available in 5 colors

# AL450WM TAIL

LED Aluminum Diving Light with Tail Switch Button

450  
lumens



Push on / off button on the bottom



3xAAA stand-alone battery holder



AL 450WM Tail LED with Glove



AL 450WM Tail LED with Pouch



AL 450WM Tail LED with Pouch and Glove

## SPECIFICATIONS

- 450 Lumens Cree LED
- Size : Dia.36 x L.122.6mm
- Aluminum Alloy, anti-corrosive anodized
- 3xAAA alkaline or Ni-MH batteries
- Angle of light beam: 40°
- Up to 4hrs of burn time
- Lanyard included
- 160g ( including batteries) weight in air
- -74g ( including batteries) buoyancy in seawater
- Switching System : Push Button

# AL450NM TAIL SPOTTER

Narrow Beam Aluminum LED Light with Tail Switch Button

450  
lumens



Push on / off button on the bottom



3xAAA stand-alone battery holder



AL 450NM Tail LED with Glove



AL 450NM Tail LED with Pouch



AL 450NM Tail LED with Pouch and Glove

## SPECIFICATIONS

- 450 Lumens Cree LED
- Size : Dia.42 x L.125.4mm
- Aluminum Alloy, anti-corrosive anodized
- 3xAAA alkaline or Ni-MH batteries
- Angle of light beam: 8°
- Up to 4hrs of burn time
- Lanyard included
- 185g ( including batteries) weight in air
- -79g ( including batteries) buoyancy in seawater
- Switching System : Push Button



# AL1200NP TAIL II

Li ion Rechargeable Battery Narrow Beam LED Light with Tail Switch Button



Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color



4 Levels of brightness and SOS controlled by a reliable push button design



Protective case for AL 1200NP Tail II. Sold separately.



Our light can fit in glove or pouch. Sold separately.



FILREDNP Red filter for AL1200NP Tail II. Sold separately.



BATCELL 18650 Li ion Rechargeable Battery



Come with random color outdoor dry bag

## SPECIFICATIONS

Light source	XML LED
Light output	120 Lm (level I), 300 Lm (level II) 600 Lm (level III), 1200 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 18650
Angle of light beam	10° narrow beam
Color temperature	6500K
Burn time	2 hrs (level IV), 5 hrs (level III) 10 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 33.2 x L. 152.2 mm
Weight in air	189 g (including battery)
Buoyancy in seawater	-87 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included

# AL1200WP TAIL II

Li ion Rechargeable Battery Wide Beam LED Light with Tail Switch Button



Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color



4 Levels of brightness and SOS controlled by a reliable push button design



Comes with the clip for easy system setup



Snoot connector for AL1200WP Tail II. Sold separately.



Our light can fit in glove or pouch. Sold separately.



FILRED 35  
Removable red and yellow filters enhances focusing performances and warm color tone



Protective case for AL 1200WP Tail II. Sold separately.



BATCELL 18650 Li ion Rechargeable Battery



Come with random color outdoor dry bag

## SPECIFICATIONS

Light source	XML LED
Light output	120 Lm (level I), 300 Lm (level II) 600 Lm (level III), 1200 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 18650
Angle of light beam	85° wide beam
Color temperature	6500K
Burn time	2 hrs (level IV), 5 hrs (level III) 10 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 35.5 x L. 137.7 mm
Weight in air	177 g (including battery)
Buoyancy in seawater	-88 g (including battery)
Switching system	Push button with battery indicator
Front glass	Concave lens
Lanyard	Included



# AL1100 RAFO II

Li ion Rechargeable Battery  
Wide Beam LED Light with  
Auto-Flash Off Function



## SPECIFICATIONS

Light source	XML LED + 2 x XPE Red LED
Light output	110 Lm (level I), 275 Lm (level II) 550 Lm (level III), 1100 Lm (level IV)
Light output (Red color mode)	150 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 18650
Angle of light beam	55° wide beam
Color temperature	6500K
AFO interval	0.2sec. +/- 0.1 sec.
Burn time	2 hrs (level IV), 5 hrs (level III) 10 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 42.4 x L. 128.3 mm
Weight in air	242 g (including battery)
Buoyancy in seawater	-129 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



Battery level indicator  
built-in: Blue color /  
Green color /  
Red color /  
Flash Red color



4 levels of brightness,  
1 level of brightness of  
Red color mode and  
SOS controlled by a  
reliable push button  
design



Comes with ball joint  
for easy system setup



Automatic Flash Off  
Function AFO interval:  
0.2 sec. +/- 0.1 sec.



Built-in red color  
led enhances  
focusing  
performance



BATCELL 18650 Li ion  
Rechargeable Battery



Come with  
random color  
outdoor dry bag

# RGB WHITE II

Li ion Rechargeable Battery  
4 Colors LED Light



Battery level indicator  
built-in: Blue color /  
Green color / Red color /  
Flash Red color



4 colors of light and  
SOS controlled by a  
reliable push button  
design



Built-in red color Led



Comes with the clip for  
easy system setup



Built-in green color Led



Snoot Connector for  
RGB White II.  
Sold separately.



Built-in blue color Led



BATCELL 18650 Li ion  
Rechargeable Battery



Come with  
random color  
outdoor dry bag


## SPECIFICATIONS

Light source	LED
Light output	500 Lm (white), 120 Lm (red) 40 Lm (blue), 300 Lm (green)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 18650
Angle of light beam	85° wide beam
Color temperature	6500K
Burn time	2 hrs
Maximum depth	100 m tested
Size	Dia. 35.5 x L. 126.3 mm
Weight in air	162 g (including battery)
Buoyancy in seawater	-84 g (including battery)
Switching system	Push button with battery indicator
Front glass	Concave lens
Lanyard	Included



# AL1200NP II

Li ion Rechargeable Battery  
Narrow Beam LED Light



Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color



4 Levels of brightness and SOS controlled by a reliable push button design



Protective case for AL 1200NP II. Sold separately.



Our light can fit in glove or pouch. Sold separately.



FILREDNP Red filter for AL1200NP II. Sold separately.



BATCELL 18650 Li ion Rechargeable Battery



Come with random color outdoor dry bag

## SPECIFICATIONS

Light source	XML LED
Light output	120 Lm (level I), 300 Lm (level II) 600 Lm (level III), 1200 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 18650
Angle of light beam	10° narrow beam
Color temperature	6500K
Burn time	2 hrs (level IV), 5 hrs (level III) 10 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 33.2 x L. 139.8 mm
Weight in air	168 g (including battery)
Buoyancy in seawater	-76 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included

# AL1200WP II

Li ion Rechargeable Battery  
Wide Beam LED Light



Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color



4 Levels of brightness and SOS controlled by a reliable push button design



Comes with the clip for easy system setup



FILRED 35 FILRED 35 Removable red and yellow filters enhances focusing performances and warm color tone



Our light can fit in glove or pouch. Sold separately.



Snoot Connector for AL1200WP II. Sold separately.



Protective case for AL 1200WP II. Sold separately.



BATCELL 18650 Li ion Rechargeable Battery



Come with random color outdoor dry bag


## SPECIFICATIONS

Light source	XML LED
Light output	120 Lm (level I), 300 Lm (level II) 600 Lm (level III), 1200 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 18650
Angle of light beam	85° wide beam
Color temperature	6500K
Burn time	2 hrs (level IV), 5 hrs (level III) 10 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 35.5 x L. 126.3 mm
Weight in air	162 g (including battery)
Buoyancy in seawater	-84 g (including battery)
Switching system	Push button with battery indicator
Front glass	Concave lens
Lanyard	Included



# AL1200xWP II

Li ion Rechargeable Battery Extra  
Wide Beam LED Light




# LIGHT HEAD

## SPECIFICATIONS

Light source	XML LED
Light output	120 Lm (level I), 300 Lm (level II) 600 Lm (level III), 1200 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 18650
Angle of light beam	120° wide beam
Color temperature	6500K
Burn time	2 hrs (level IV), 5 hrs (level III) 10 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 35.5 x L 122.1 mm
Weight in air	160 g (including battery)
Buoyancy in seawater	-84 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



Battery level indicator  
built-in: Blue color /  
Green color / Red color /  
Flash Red color



4 Levels of brightness  
and SOS controlled by  
a reliable push button  
design



FILYEL 35 FILRED 35  
Removable red and  
yellow filters enhances  
focusing performances  
and warm color tone



Snoot Connector for  
AL1200XWP II.  
Sold separately.



BATCELL 18650 Li ion  
Rechargeable Battery



Comes with the clip  
for easy system setup



Our light can fit in  
glove or pouch. Sold  
separately.



Protective case for  
AL 1200XWP II.  
Sold separately.



Come with  
random color  
outdoor dry bag

Light heads can fit for VTL 3800P & TL 3500P.

Light heads can fit for VL 4200P,  
VTL 2600P & TL2600P



TL 3500PLH



VL 4200PLH



VTL 2600PLH



VTL 3800PLH



TL 2600PLH



CB 9000PLH



CB 6500PLH



VTL 8000PLH



Light heads can fit for  
CB 6500P & CB 9000P.

Light heads can fit for VTL 8000P, TL 4800P,  
VL 10000P, VL 8000P Tri Color.



VL 10000PLH  
VL 8000PLH Tri Color



TL 4800PLH



AL 1200NPLH II



AL 1200WPLH II



AL 1200XWPLH II



AL 1100RAFOLH II



RGB White LH II



Light heads can fit for AL 1200NP II, AL 1200WP II, AL 1200XWP II, AL 1100RAFO II & RGB White II.



# BLACK MOLLY IV AL1800XWP II TRI COLOR



Available in 2 colors

## SPECIFICATIONS

Light source	4 x XML LED + 2 x XPE Red LED
Light output (Cool white mode)	450Lm (level I), 900 Lm (level II) 1800 Lm (level III)
Light output (Warm white mode)	450Lm (level I), 900 Lm (level II) 1800 Lm (level III)
Light output (Red color mode)	150 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 26650
Angle of light beam	120° wide beam
Color temperature	6500K cool white and 5500K warm white
Burn time	2 hrs (level III), 4 hrs (level II) and 8 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 35.5 x L 126.8 mm
Weight in air	218 g (including battery)
Buoyancy in seawater	-105 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



Built-in red color led enhances focusing performance



Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color



Built in yellow color led enhances warmer color tone



Protective case for AL 1800XWP Tri Color II and Single Arm Tray. Sold separately.



3 Levels of brightness for cool white mode, 3 Levels of brightness for warm white mode. 1 level of brightness of Red color mode and SOS controlled by a reliable push button design



BATCELL26650 Li ion Rechargeable Battery



Comes with ball joint for easy system setup



Protective case for AL 1800XWP Tri Color II. Sold separately.



Come with random color outdoor dry bag

# BLACK MOLLY V AL2600XWP II



Available in 2 colors

## SPECIFICATIONS

Light source	4 x XML LED + 2 x XPE Red LED
Light output	260 Lm (level I), 650 Lm (level II) 1300 Lm (level III), 2600 Lm (level IV)
Light output (Red color mode)	150 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 26650
Angle of light beam	120° wide beam
Color temperature	6500K
Burn time	2 hrs (level IV), 4 hrs (level III) 8 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 35.5 x L 126.8 mm
Weight in air	218 g (including battery)
Buoyancy in seawater	-105 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



Built-in red color led enhances focusing performance



Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color



BATCELL26650 Li ion Rechargeable Battery



Protective case for AL 2600XWP II and Single Arm Tray. Sold separately.



4 levels of brightness, 1 level of brightness of Red color mode and SOS controlled by a reliable push button design



Removable yellow filter enhances warmer color tone



Comes with ball joint for easy system setup



Protective case for AL 2600XWP II. Sold separately.



Come with random color outdoor dry bag



# CF450 II



Available in 2 colors

## SPECIFICATIONS

Light source	Cree LED
Light output	450 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	3xAAA alkaline or Ni-MH batteries
Angle of light beam	7° to 37°adjustable
Color temperature	6500K
Burn time	Up to 4hrs
Maximum depth	100 m tested
Size	Dia. 35.5 x L. 131.9mm
Weight in air	216 g (including batteries)
Buoyancy in seawater	-104 g (including batteries)
Switching system	Magnetic Swivel
Front glass	Tempered optical glass & Convex Lens
Lanyard	Included



Twist the front to change the focus (Turning force increases with depth)



Magnetic Swivel Switch allows for one hand operation



CF 450 II LED with Glove



3xAAA stand-alone battery holder



CF 450 II LED with Pouch



CF 450 II LED with Pouch and Glove

# CF1200P II




Li ion Rechargeable Battery  
Changeable Focus LED Light



## SPECIFICATIONS

Light source	XML LED
Light output	120 Lm (level I), 300 Lm (level II) 600 Lm (level III), 1200 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 18650
Angle of light beam	7° narrow beam to 37° wide beam
Color temperature	6500K
Burn time	2 hrs (level IV), 5 hrs (level III) 10 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 35.5 x L. 169.3mm
Weight in air	245 g (including battery)
Buoyancy in seawater	-121 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color



4 Levels of brightness and SOS controlled by a reliable push button design



Twist the front to change the focus (Turning force increases with depth)



BATCELL 18650 Li ion Rechargeable Battery



Come with random color outdoor dry bag



# HL450N

Narrow Beam LED Head Light

450  
lumens



## SPECIFICATIONS

Light source	Cree LED
Light output	45 Lm (level I), 113 Lm (level II) 225 Lm (level III), 450 Lm (level IV)
Casing material	Aluminum alloy light head and Polycarbonate body
Power source	3 x AAA alkaline batteries
Angle of light beam	8° narrow beam
Color temperature	6500K
Burn time	2 hrs (level IV), 4 hrs (level III) 8 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 36.8 x L. 84.4 mm with light head dia. 41 mm
Weight in air	187 g (including batteries)
Buoyancy in seawater	-56 g (including batteries)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass



4 levels of brightness  
and SOS controlled by  
a reliable push button  
design



3 x AAA alkaline  
batteries



Battery level indicator  
built-in: Blue color /  
Green color / Red  
color / Flash Red color



FILREDHLN Red  
filter for HL 450N.  
Sold separately.

# HL450xw

Extra Wide Beam LED Head Light

450  
lumens



## SPECIFICATIONS

Light source	2 x Cree LED +2 x XPE Red LED
Light output	45 Lm (level I), 113 Lm (level II) 225 Lm (level III), 450 Lm (level IV) 100 Lm
Light output (Red color mode)	
Casing material	Aluminum alloy light head and Polycarbonate body
Power source	3 x AAA alkaline batteries
Angle of light beam	120° wide beam
Color temperature	6500K
Burn time	2 hrs (level IV), 4 hrs (level III) 8 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 36.8 x L. 84.4 mm with light head dia. 38.8 mm
Weight in air	189 g (including batteries)
Buoyancy in seawater	-58 g (including batteries)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass



Built-in red color led  
enhances focusing  
performance



4 levels of brightness,  
1 level of brightness of  
Red color mode and  
SOS controlled by a  
reliable push button  
design



Battery level indicator  
built-in: Blue color /  
Green color / Red  
color / Flash Red color



3 x AAA alkaline  
batteries

# HL1000N

Li ion Rechargeable Battery  
Narrow Beam LED Head Light

1000  
lumens



## SPECIFICATIONS

Light source	Cree LED
Light output	100 Lm (level I), 250 Lm (level II) 500 Lm (level III), 1000 Lm (level IV)
Casing material	Aluminum alloy light head and Polycarbonate body
Power source	Li ion Rechargeable battery pack BATCELL18650
Angle of light beam	8° narrow beam
Color temperature	6500K
Burn time	2 hrs (level IV), 4 hrs (level III) 8 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 36.8 x L. 84.4 mm with light head dia. 41mm
Weight in air	205 g (including battery)
Buoyancy in seawater	-74 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass



4 levels of brightness  
and SOS controlled by  
a reliable push button  
design



Battery level indicator  
built-in: Blue color /  
Green color / Red  
color / Flash Red color



BATCELL18650 Li ion  
Rechargeable Battery



FILREDHLN Red filter  
for HL 1000N.  
Sold separately.

# HL1000xw

Li ion Rechargeable Battery  
Extra Wide Beam LED Head Light

1000  
lumens



## SPECIFICATIONS

Light source	2 x Cree LED +2 x XPE Red LED
Light output	100 Lm (level I), 250 Lm (level II) 500 Lm (level III), 1000 Lm (level IV)
Light output (Red color mode)	150 Lm
Casing material	Aluminum alloy light head and Polycarbonate body
Power source	Li ion Rechargeable battery pack BATCELL18650
Angle of light beam	120° wide beam
Color temperature	6500K
Burn time	2 hrs (level IV), 4 hrs (level III) 8 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 36.8 x L. 84.4 mm with light head dia. 38.8mm
Weight in air	207 g (including battery)
Buoyancy in seawater	-76 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass



Built-in red color led  
enhances focusing  
performance



4 levels of brightness,  
1 level of brightness of  
Red color mode and  
SOS controlled by a  
reliable push button  
design



Battery level indicator  
built-in: Blue color /  
Green color / Red  
color / Flash Red color



BATCELL18650 Li ion  
Rechargeable Battery



## EASY CLIP RAINBOW COLOR LIGHT



### SPECIFICATIONS

- Available fifteen color output – Red, Green, Orange, Blue, Purple, Yellow, Light Blue, Flash red, Flash green, Flash orange, Flash blue, Flash purple, Flash yellow, Flash light blue automatically run all fourteen modes.
- 12-24 hrs of burn time
- 2 x CR2032 batteries
- Dia. 32 x L. 38mm
- 100 meter tested
- Lanyard included
- 23g ( including batteries) weight in air
- -3g ( including batteries) buoyancy in seawater

## EASY CLIP LIGHT WITH FLASH



### SPECIFICATIONS

- Available six color output – Blue, Red, Green, Flash Blue, Flash Red, Flash Green,
- Up to 36 hrs of burn time
- 2 x CR2032 batteries
- Dia. 32 x L. 38mm
- 100 meter tested
- Lanyard included
- 23g ( including batteries) weight in air
- -3g ( including batteries) buoyancy in seawater

Easily clip the light on the  
goggle, mask, belt and etc.



# COMBO PACK SERIES

**AL 450 NM Tail Spotter**  
Narrow Beam Aluminum LED Light with  
Tail Switch Button

**AL 1200NP II**  
Li Ion Rechargeable Battery Narrow  
Beam LED Light

**Easy Clip Rainbow Color light**



**AL 450 NM Tail Spotter**  
Narrow Beam Aluminum LED Light with  
Tail Switch Button

**AL 1200WP II**  
Li Ion Rechargeable Battery Wide  
Beam LED Light

**Easy Clip Rainbow Color light**



**AL 250**  
Multi-Function Aluminum LED Light

**AL 1200NP II**  
Li Ion Rechargeable battery  
Narrow Beam LED Light

**Easy Clip Rainbow Color light**



**AL 450 WM Tail**  
LED Aluminum Diving Light with  
Tail Switch Button

**AL 1200NP II**  
Li Ion Rechargeable Battery Narrow  
Beam LED Light

**Easy Clip Rainbow Color light**



**AL 450 WM Tail**  
LED Aluminum Diving Light with  
Tail Switch Button

**AL 1200WP II**  
Li Ion Rechargeable Battery Wide  
Beam LED Light

**Easy Clip Rainbow Color light**



**AL 250**  
Multi-Function Aluminum LED Light

**AL 1200WP II**  
Li Ion Rechargeable battery  
Wide Beam LED Light

**Easy Clip Rainbow Color light**





# GREEN SPOT LIGHT RED SPOT LIGHT



Operate with  
2 x AAA batteries



CLIPMNTSPOT  
Mounting clip for Green Spot Light  
and Red Spot Light. Sold separately.

## SPECIFICATIONS

## GREEN SPOT LIGHT

Light source	: Green Laser
Light output	: Below 1 mW
Casing material	: Aluminum alloy. Anti-corrosive anodized
Power source	: 2 x AAA alkaline or Ni-MH batteries
Wavelength	: 520nm
Burn time	: Up to 24 hrs
Maximum depth	: 100 m tested
Size	: Dia. 19 x L 168.6 mm
Weight in air	: 89 g (including batteries)
Buoyancy in seawater	: -54 g (including batteries)
Switching system	: Twisting Bezel
Front glass	: Tempered optical glass
Lanyard	: Included

## RED SPOT LIGHT

Light source	: Red Laser
Light output	: Below 1 mW
Casing material	: Aluminum alloy. Anti-corrosive anodized
Power source	: 2 x AAA alkaline or Ni-MH batteries
Wavelength	: 650nm
Burn time	: Up to 24 hrs
Maximum depth	: 100 m tested
Size	: Dia. 19 x L 154.1 mm
Weight in air	: 82 g (including batteries)
Buoyancy in seawater	: -51 g (including batteries)
Switching system	: Twisting Bezel
Front glass	: Tempered optical glass
Lanyard	: Included

# PROTECTIVE CASE SERIES



Model :	PC101 A	PC102 A	PC103 A	PC104 A	PC105 A	PC106 A
Outer Dimension :	225 x 180 x 100 mm	350 x 270 x 120 mm	340 x 310 x 120 mm	360 x 285 x 190 mm	420 x 360 x 130 mm	420 x 360 x 190 mm
Inner Dimension :	200 x 135 x 85 mm	325 x 210 x 110 mm	310 x 250 x 107 mm	330 x 270 x 175 mm	380 x 310 x 120 mm	380 x 310 x 180 mm
Case can fit for :	AL1200NP II, AL1200WP II, AL1200XWP II, CF1200P II, Black Molly IV, Black Molly V, AL1200NP Tail II, AL1200WP Tail II, AL1100RAFO II, RGB White II	VL4200P, VTL3800P, TL3500P, TL3500P Supreme, VTL2600P, TL2600P VL10000P, VL8000P Tri Color, VTL8000P, TL4800P, TL8000P, CB6500P, CB9000P, CB15000P, VL15000P Pro Mini, VL15000P Pro Mini TC, VL33000P II	TL4800PC Slim, VTL8000PC Slim	All Purpose	Go Pro Tray Kit Set	All Purpose




# FLUORODIVE KIT SETS

Science has discovered corals contain Fluorescent Proteins invisible to the naked eye that jump into view using innovative high-intensity fluorolights and filters.

Bigblue Fluorodive Kits provide everything you need to experience this incredibly beautiful effect. You get specially designed filters to precisely match the coral fluorescence wavelength, and yellow blue-barrier filters to increase the intensity of the colors emitted by the corals. Our innovative design is the only one that allows you to easily switch between blue and white light to accommodate changes in dive conditions.

These kits are suitable for night divers, resorts, science institutions, ecological monitoring groups and specialty photographers.

Truly there is nothing that can match the beauty of witnessing coral fluorescence on your next night dive!



## CAMERA FILTERS

Camera filters are available for you to capture the macro or wide angle photos or videos of the memorable aquatic creatures.

Photos of the fluorescence stimulated by the specific wavelength and captured through a barrier filter

## FDK38

CF450 / CF1200P / AL1200WP / AL1200XWP / AL1200WP Tail / BLACK MOLLY II / BLACK MOLLY III Fluorodive Kit



BLUE FILTER

YELLOW MASK

## FILFLUOR015000

Fluorodive filter for VL 15000P Pro Mini / VL 15000P Pro Mini Tri Color / CB15000P



## FDK35

CF450 II / CF1200P II / AL1200WP II / AL1200XWP II / AL1200WP Tail II / BLACK MOLLY IV / BLACK MOLLY V Fluorodive Kit



BLUE FILTER

YELLOW MASK

## FDK55

VTL3800P / VL10000P VL8000P Tri Color Fluorodive Kit



BLUE FILTER

YELLOW MASK

## FDK63

CB6500P / CB9000P / VTL8000P Fluorodive Kit



BLUE FILTER

YELLOW MASK

## FDK44

VL4200P / VTL2600P Fluorodive Kit



BLUE FILTER

YELLOW MASK



## CAMERA TRAY 27



Camera Tray 27 with 27cm long tray.  
Two 1" Ball joint arms with no-slip grip.  
Compatible with Olympus TG4/TG5 Housings.

## BBGPTRAY

Go Pro Tray



Go Pro  
Hot Shoe Adapter



## GO PRO KIT SETS

### GP4200 Kit

- 1 pc. of Double Clip (CLP02)
- 1 pc. of Go Pro Tray (BBGPTRAY)
- Light not included



### GP1200 Kit

- 2 pcs. of Double Clip (CLP02)
- 2 pcs. of Sea & Sea Standard (DA009)
- 1 pc. of Go Pro Tray (BBGPTRAY)
- Lights not included



### GP450 Kit

- 2 pcs. of Mounting Clip (CLIPMINTCF)
- 2 pcs. of Double Clip (CLP02)
- 2 pcs. of Sea & Sea Standard (DA009)
- 1 pc. of Go Pro Tray (BBGPTRAY)
- Lights not included



### Protective Case for Go Pro Tray Kit Set

- 1 pcs. of ALI200WVP II
- 1 pcs. of ALI200XWVP II
- 2 pcs. of Double Clip (CLP02)
- 2 pcs. of Sea & Sea Standard (DA009)
- 1 pc. of Go Pro Tray (BBGPTRAY)



## EXTENDGPTRAY

Extendable Go Pro Tray



## SINGLEARMTRAY

Single Arm Go Pro Tray



## FLEXIGPTRAY

7" Flexi Arm Go Pro Tray



## FLEXISINGLEARMTRAY

7" Flexi Arm Single Arm Tray



## FLEXIEXTENDGPTRAY

7" Flexi Arm Extendable  
Go Pro Tray



# BATTERIES & CHARGERS



**BATCELL18650**

Battery for AL1200NP II / AL1200WP II / AL1200XWP II / AL1200NP Tail II / AL1200WPTail II / CF1200P II / AL1100RAFO II / HL1000XW / HL1000N / RGB White II



**BATCELL26650**

Battery for Black Molly IV / Black Molly V



**BATCELL32650**

Battery for VL4200P / VTL3800P / TL3500P / VTL2600P / TL2600P



**BATCELL18650x4**

Battery for VL10000P / VTL8000P / TL4800P / VL8000P Tri Color



**BATCELL21700x4**

Battery for CB6500P / CB9000P



**BATCELL18650x7**

Battery for VL15000P Pro Mini / VL15000P Pro Mini Tri Color / CB15000P / TL8000P



**CR2032**

Battery for Easy Clip Light



**BATCELL18650x8**

Battery for TL4800PC Slim / VTL8000PC Slim



**BATCELL18650x4SUPREME**

Battery for TL3500P Supreme



**BATCELL21700x8**

Battery for VL33000P II



**BATCHR18650x4**

Charger for VL10000P / VTL8000P / TL4800P / VL8000P Tri Color



**BATCHR21700x4**

Charger for CB6500P / CB9000P



**BATCHR18650x4 SUPREME**

Charger for TL3500P Supreme



**BATCHR21700x8**

Charger for VL33000P II



**BATCHR18650x7**

Charger for VL15000P Pro Mini / VL15000P Pro Mini Tri Color / CB15000P / TL8000P



**BATCHR32650/26650**

Charger for VL4200P / VTL3800P / TL3500P / Black Molly IV / Black Molly V / VTL2600P / TL2600P



**BATCHR18650x8**

Charger for TL4800PC Slim / VTL8000PC Slim



**BATCHR18650**

Charger for AL1200NP II / AL1200WP II / AL1200XWP II / AL1200NP Tail II / AL1200WPTail II / CF1200P II / AL1100RAFO II / HL1000XW / HL1000N / RGB White II

# ACCESSORIES



**TLGGLOVE**

Goodman glove for TL2600P / VTL2600P / TL3500P Supreme / VL4200P / VTL3800P / TL3500P / VL10000P / VTL8000P / TL4800P / VL8000P Tri Color / CB6500P / CB9000P / Black Molly IV / Black Molly V



**NPGGLOVE**

Neoprene glove for Mini Light



**NPGGLOVE**

Neoprene glove for AL1200NP II / AL1200WP II / AL1200XWP II / AL1200NP Tail II / AL1200WPTail II



**PISTOLGRIPHANDLE**

Pistol Grip Handle for Black Molly IV / Black Molly V / TL2600P / VTL2600P / TL3500P / VTL3800P / TL3500P Supreme / VL4200P / CB6500P / CB9000P / VL10000P / VL8000P Tri Color / VTL8000P / TL4800P / TL8000P / VL15000P Pro Mini / VL15000P Pro Mini Tri Color / CB15000P



**SIDEMOUNTCONNECTOR CABLE-90**

90 degree sidemount connector cable for TL4800PC Slim / VTL8000PC Slim




**CONNECTOR CABLE-180**

180 degree connector cable for TL4800PC Slim / VTL8000PC Slim



**LNTHANDLE**

Lantern style handle



**GHA-01C**

Goodman handle with connector for TL2600P / TL3500P / TL4800P / TL4800PC Slim / VTL8000PC Slim / TL3500P Supreme / TL8000P



**SFGHA-01C**

Slim fit Goodman handle with connector for TL2600P / TL3500P / TL4800P / TL4800PC Slim / VTL8000PC Slim / TL3500P Supreme / TL8000P



# ACCESSORIES



**SNOOT 35**

Snoot Connector for  
AL1200WP II / AL1200XWP II /  
AL1200WP Tail II / RGB White II



**SNOOT 38**

Snoot Connector for  
AL1200WP / AL1200XWP /  
AL1200WP Tail / RGB White



**SNOOT 55**

Snoot Connector for  
VL6000P



**CLIPMNTSPOT**

Mounting clip for  
Green Spot Light / Red Spot Light



**CLIPMNTAL**

Mounting clip for AL1200WP II /  
AL1200XWP II / CF1200P II




**CLIPMNTCF**

Mounting clip for CF450 II /  
AL450WM Tail / AL1200WP Tail II



**SNOOT 63**

Snoot Connector for  
CB6500P / CB9000P



**FILFLUORO 15000**

Fluorodive filter for  
CB15000P / VL15000P Pro Mini /  
VL15000P Pro Mini Tri Color



**FDMASKYL**

Yellow filter for Fluorodiving



**GO PRO MOUNT**

Go Pro Mount for  
Go Pro Camera



**1" BALL JOINT**

1" Ball Joint fit for Black Molly IV / Black Molly V  
VTL2600P / VL4200P / VTL3800P / VL8000P Tri Color / VL10000P /  
VL4200P / VTL 8000P / CB6500P / CB9000P / VL33000P II /  
VL15000P Pro Mini / VL15000P Pro Mini Tri Color / CB15000P



**FILRED35**

Red filter for AL1200WP II /  
AL1200XWP II /  
AL1200WP Tail II



**FILREDSM**

Red filter for AL1200WP /  
AL1200XWP /  
AL1200WP Tail



**FILREDNP**

Red filter for AL1200NP II /  
AL1200NP Tail II



**FILREDHLN**

Red filter for HL1000N /  
HL450N



**SPRING CORD**

Length : 330mm



**EASY RELEASE MOUNT**

Easy Release Mount fit for  
helmet / DPV



**FILYELG**

Yellow filter for  
VTL3800P / VL10000P



**FILYELSM**

Yellow filter for  
AL1200WP /  
AL1200XWP /  
AL1200WP Tail /  
Black Molly III



**FILYEL35**

Yellow filter for  
AL1200WP II /  
AL1200XWP II /  
AL1200WP Tail II /  
Black Molly V



**FILYEL44**

Yellow filter for  
VL4200P / VTL2600P



**FILYEL63**

Yellow filter for  
VTL8000P /  
VTL8000PC Slim



**NPHOODMS**

Neoprene hood for one  
light holster



**NPHOODMD**

Neoprene hood for two  
light holster



**NPRPOUCH**

Neoprene pouch with  
retractor for AL1200NP II /  
AL1200WP II / AL1200XWP II /  
AL1200NP Tail II / AL1200WP Tail II



**NPRPOUCHM**

Neoprene pouch with  
retractor for Mini Light

## ACCESSORIES

### Outdoor Dry Bags



3L	5L	7L
Dia. 140 x L. 330 mm	Dia. 170 x L. 380 mm	Dia. 180 x L. 510 mm
Available in 5 colors Yellow, Green, Pink, Light Blue, Blue	Available in 5 colors Yellow, Green, Pink, Light Blue, Blue	Available in 6 colors Yellow, Green, Pink, Light Blue, Blue, Black

## EASY RELEASE MOUNT SERIES



## PHOTO/VIDEO ARMS & ACCESSORIES

### Float Arms Series



9" Float Arm

Dia. 70 x 228mm  
Weight above water : 281g  
Buoyancy lift : 360g



13" Float Arm

Dia. 70 x 330mm  
Weight above water : 430g  
Buoyancy lift : 612g

### Flexi Arms Series



7" Flexi Arm



9" Flexi Arm



6" Flexi Arm  
Hot Shoe YS Adapter



6" Flexi Arm  
Hot Shoe Ball Adapter



YS Adapter



# PHOTO/VIDEO ARMS & ACCESSORIES

## Clips

- Made of T6061 grade aluminum
- Available in 2 versions: double clip and a triple clip
- Ergonomic handle makes it easy to twist on and off



CLP 02 Double clip



CLP 03 Triple clip

## Arms

- Full T6061 grade aluminum
- Available in 4 lengths: 5", 8", 12", 16"



5" Arm



8" Arm



12" Arm



16" Arm

For 1" ball joint to connect to extend the connection



# DA SERIES



DA001

Hot Shoe Adapter



DA002

Sea & Sea Adapter



DA003

Light & Motion Adapter



DA004

Standard Dovetail Plate



DA005

8mm Thread



DA006

Sea & Sea Light Adapter



DA007

Sea & Sea Hot Shoe Adapter



DA008

Sea & Sea Medium



DA009

Sea & Sea Standard



DA010

Base Plate Ball Mount



DA011

T-Groove Adapter



DA012

Universal Mount Base



DA013F

1/4" Thread Adapter



DA013M

1/4" Thread Adapter



DA014

Ikelite 200 Strobe Adapter



DA015

Single Ball Arm with Sea & Sea Adapter



DA016

UK Light Adapter



DA017

Standard Dovetail



DA018

Iron Z Series Strobe Adapter



DA022

Slot Stay



DA023

6mm Thread Adapter

Specifications subject to change without prior notice.



## OUR DISTRIBUTORS & DEALERS

### Australia Distributor : Adreno

Contact Person : Robbie Lewis  
E-mail : robbie@adreno.com.au  
Phone : 61-07-3391-2299  
Mail : 54-58 Deshon Street, Woolloongabba,  
Brisbane, QLD 4102, Australia

### Austria Distributor : Custom Diving Systems

Contact Person : Yannig Charles  
E-mail : contact@cds-pro.com  
Phone : +33 0 6 114 81 114  
Mail : 1143 Route De La Jiraz - 73120  
Courchevel, France

### Belgium/ Netherlands / Luxembourg Distributor : Custom Diving Systems

Contact Person : Yannig Charles  
E-mail : contact@cds-pro.com  
Phone : +33 0 6 114 81 114  
Mail : 1143 Route De La Jiraz - 73120  
Courchevel, France

### Brazil Distributor : Seasub

Contact Person : Pablo Y. Varela  
E-mail : pablo@seasub.com.br  
Phone : 55-11-38328342  
Mail : Rua Baumann, 1039/1051,  
Cep 05318000,  
Sao Paulo, Brazil

### Canada Distributor : Pacific Scuba Industries

Contact Person : Michael Joseph &  
Laura Valente  
E-mail : laurabigblue@outlook.com  
Phone : 778-245-1962  
Mail : 31519 Southern Dr, Abbotsford,  
BC V2T5P1, Canada

### Czech Republic Distributor : Olson S.R.O

Contact Person : Ing. Barbora Peskova  
E-mail : peskova@olson.cz  
Phone : 420 602 376 896  
Mail : Holesovicka Trznice, Hala C.16  
Bubenske Nabrezi 306/13  
170 04 Praha 7  
Czech Republic

### France / Europe Distributor : Custom Diving Systems

Contact Person : Yannig Charles  
E-mail : contact@cds-pro.com  
Phone : +33 (0) 6 114 81 114  
Mail : 1143 Route De La Jiraz - 73120  
Courchevel, France

### Germany Distributor : Custom Diving Systems

Contact Person : Yannig Charles  
E-mail : contact@cds-pro.com  
Phone : +33 (0) 6 114 81 114  
Mail : 1143 Route De La Jiraz - 73120  
Courchevel, France

### Greece / Croatia Distributor : Custom Diving Systems

Contact Person : Yannig Charles  
E-mail : contact@cds-pro.com  
Phone : +33 (0) 6 114 81 114  
Mail : 1143 Route De La Jiraz - 73120  
Courchevel, France

### Indonesia Distributor : Divesea Indonesia

Contact Person : Chatra Hapsoro  
E-mail : bigblue.id@gmail.com  
Phone : 62-82145490450  
Mail : Metro Park Residence, Unit MA-LG-05,  
JL. Pilar Mas Utama Raya Kav 28,  
Kebon Jeruk, Jakarta Barat 11520 Indonesia

### Italy/ Malta Distributor : Custom Diving Systems

Contact Person : Yannig Charles  
E-mail : contact@cds-pro.com  
Phone : +33 (0) 6 114 81 114  
Mail : 1143 Route De La Jiraz - 73120  
Courchevel, France

### Japan Distributor : Zero Co., Ltd.

Contact Person : Katsuhiko Saotome  
E-mail : zero@zero-zero.co.jp  
Phone : 81-3-5721-1906  
Fax : 81-3-5721-1910  
Mail : 1-11-5 Takaban, Meguro-Ku,  
Tokyo, Japan

### Korea Distributor : King Sports

Contact Person : Mr. Chang / Yun Hee Chang  
E-mail : kingdive@kingsports.co.kr  
Phone : 82-2-3628251  
Mail : 35-4, 1GA, Manri-Dong, Chung-Gu,  
Seoul, Korea

### Kuwait Dealer : Ilmunz Marine Co.

Contact Person : Abdulrahman Al-Serheed  
E-mail : ilmunz@ilmunz.com  
Phone : +965 95500969  
Mail : Creative Design Center, Block 1, Street 10,  
Building 63, Store 2.2,  
Shuwaikh Industrial 1, Kuwait

### Malaysia Distributor : Rainbow Runner Sdn Bhd

Contact Person : Sim  
E-mail : ops@rainbowrunner.net  
Phone : 60-341-622837  
Fax : 60-341-617837  
Mail : 5, Ukay Boulevard, Jalan Lingkaran  
Tengah 2, Hulu Kelang, 68000 Ampang,  
Selangor, Malaysia

### Maldives Dealer : Sea Gear

Contact Person : Hussien Abdulla  
E-mail : sales@seagear.com.mv  
Phone : +960 3302737  
Mail : M. Araliya - Ground Floor - Alhivila Magu,  
20292 Male, Maldives

### Mexico Distributor : Comercializadora UNIF Sa De CV

Contact Person : Tristan Termat  
E-mail : tristan@unifmexico.com.mx  
Phone : + 52 984 80 311 68  
Mail : Calle 4 nte Mza 42 Lote 4-1 Local B Entre  
25 y 30 Avenida Col. Centro Localidad :  
Playa del Carmen, Q. Roo Municipio :  
Solidaridad CP: 77710 Mexico

### New Zealand Distributor : Sea Tech Ltd.

Contact Person : Dave Moran  
E-mail : info@seatech.co.nz  
Phone : 64-9-5210684  
Mail : 47 Tautari St. Orakei, Auckland 1071,  
New Zealand

### Philippines Distributor : Dive Supply Subic, INC.

Contact Person : Rowena Merto  
E-mail : muriel@aquaventurewhitetip.com  
Phone : 63-2-708-9996  
Mail : Office 6&7 EMS Building, 14th Street  
Subic Gate Perimeter Road, Subic Bay  
Freeport Zone, Olongapo City,  
2222, Philippines

### Poland Distributor : Waterfall

Contact Person : Darek  
E-mail : darek@waterfall.pl  
Phone : 48-600-340-002  
Mail : UL. Klimczaka 22D/3, 02-797 Warszawa  
Poland PL 7621470585

### Scandinavian Distributor : AquaFun AB

Contact Person : Sales Office  
E-mail : info@aquafun.se  
Phone : 46-0-40-295-300  
Mail : Sangleksgatan 4E, 215 79, Malmö,  
Sweden

### Singapore Distributor : Divesea Pte Ltd

Contact Person : Fairuz Ahmad  
E-mail : team@divesea.com.sg  
Phone : 65-85115164  
Mail : 3 Coleman Street, #02-15,  
Peninsula Shopping Centre  
Singapore 179804

### South Africa Distributor : Manex & Power Marine

Contact Person : Gavin Jones  
E-mail : gavin.jones@manex.co.za  
Phone : 27-021-511-7292  
Mail : 9 Paarden Eiland Road, Paarden Eiland,  
South Africa

### Spain/ Portugal Distributor : Custom Diving Systems

Contact Person : Yannig Charles  
E-mail : contact@cds-pro.com  
Phone : +33 (0) 6 114 81 114  
Mail : 1143 Route De La Jiraz - 73120  
Courchevel, France

### Switzerland Distributor : Custom Diving Systems

Contact Person : Yannig Charles  
E-mail : contact@cds-pro.com  
Phone : +33 0 6 114 81 114  
Mail : 1143 Route De La Jiraz - 73120  
Courchevel, France

### Thailand Distributor : Scuba Republic Thailand

Contact Person : Woranon Samakoses  
E-mail : scubarepublicthailand@gmail.com /  
bigbluelightsthailand@gmail.com  
Phone : 66-0-617732363  
Mail : 52 Moo 8, Theparatana (Bangna - Trad) Road,  
KM. 7, Bangkaew, Bangplee,  
Samutprakarn 10540 Thailand

### Turkey Distributor : K Pro Doga Sporlari Malzemeleri Tic. Ltd. STI

Contact Person : Akin Kaftanoglu  
E-mail : akinkaftanoglu@yahoo.com  
Phone : 90-3124334479  
Mail : Bulbulderesi Cad. No: 23/A, Seyranbaglari,  
Ankara, Turkey

### U.A.E. Distributor : Senyar Marine Equipment

Contact Person : Abdulla Al Kindi  
E-mail : alastair@liquidsports.co.uk  
Phone : 971-2-666-9999  
Mail : P.O. Box 112790, Abu Dhabi, U.A.E.

### United Kingdom / Ireland Distributor : Liquid Sports Ltd.

Contact Person : Alastair Ansell  
E-mail : alastair@liquidsports.co.uk  
Phone : 44-0-7585-935522  
Mail : 11 Stag Lane, Berkhamsted,  
Hertfordshire, HP4 1FJ, UK





# bigblue®

THE BRIGHTER IDEA

---

**Headquarters :**

**Bossk International Company Limited**

Contact Person : Oscar Tong

E-mail : [oscar@bigblue.com.hk](mailto:oscar@bigblue.com.hk)

Phone : 852-3568-0773

Fax: 852-3998-3127

Mail : Room 818, 8/F, Po Yip Building, 23, Hing Yip

Street, Kwun Tong, Hong Kong

Website : [www.bigbluelights.com](http://www.bigbluelights.com)

[www.bigblue.com.hk](http://www.bigblue.com.hk)

---

**US Sales Office : BosskUSA / Bigblue Dive Lights**

Contact Person : Tim Ratcliffe

E-mail : [sales@bigbluedivelights.com](mailto:sales@bigbluedivelights.com)

Phone : 727-442-2300

Fax: 727-499-7117

Mail : 1710N Hercules Ave, Suite 103, Clearwater,  
FL 33765 USA

Visit Us  
on website



Like Us  
on facebook

